

UT8250-16SRAR

**ALUMINUM ATV UTILITY TRAILER 7X16 W/ SIDE  
LOAD RAMPS & RETAINING RAIL 5000# GVWR**



Model UT8250-16SRAR shown with optional bi-fold ramp and spare tire with pedestal and bracket.

This 7x16 ft heavy-duty tandem trailer easily hauls your ATV and UTV, with side-load ramps that are conveniently integrated into the load retaining rail, assembling in seconds. Both the standard straight rear ramp and optional bi-fold ramp fold down flat on the trailer deck for easy hauling when empty. Every Chilton Trailer is built by hand with a fully welded frame and ramps for years of reliability.

**STANDARD FEATURES**

- Integrated side load ramp for ATV
- 14.5" aluminum load retaining rail
- 5/4" pressure treated lumber deck
- Electric brakes
- Adjustable swivel jack with wheel
- Spring loaded ramp locks for easy one-person operation
- Fully welded frame & ramps, reinforced A-frame tongue
- 5000# GVWR (each axle rated for 3500#)

**OPTIONS**

- Bi-fold ramp upgrade (adds 4" to total trailer length)
- Premium deck lighting package
- Load lighting
- LED lighting upgrade
- Adjustable channel for pintle
- 2-5/16" coupler
- 1100# winch package, 20 ft strap, steel mounting pedestal
- Upgrade to radial tires load range C
- Spare tire pedestal + bracket
- Spare tire ST205/75D-15" load range C
- Radial spare tire upgrade
- Aluminum rims with radial tire upgrade
- Aluminum rim with radial spare tire

**SPECIFICATIONS**

Trailer Dimensions	102"X249"
Deck Dimensions	82"X192"
Ramp Width	78"
Retaining Rail Height	14.5"
Trailer Weight	1400#
GVWR	5000#
Carrying Capacity	3600#
Carrying Capacity (with brakes)	3600#
Tire Size	15"
Hitch Ball Size	2"



Model UT8250-16SRAR shown with optional bi-fold ramp and spare tire with pedestal and bracket.

For warranty information and to register your new trailer, visit [www.ChiltonTrailers.com/warranty-registration](http://www.ChiltonTrailers.com/warranty-registration).